Specification Sheet

BF007
FASVINYL MATT WHITE
S692N

FACE:
A monomeric, plasticised, calendered, cadmium free vinyl film. Suitable for printing by screen, flexo, gravure and letterpress and can be hotfoil stamped with suitable leaf quality.

Thickness	80 micron ±5%
Basic weight	115 gsm ±5%

ADHESIVE:
S692N A clear permanent acrylic adhesive, featuring excellent UV resistance and weatherability, together with good adhesion performance, even on apolar substrates.

Initial Tack	High
Final Adhesion	High
Min. App.Temp	+5°C
Temp Range	-20°C to +80°C
UV Resistance	Excellent

The adhesive complies with FDA 175.105 and with BgVV recommendations for direct contact with dry and moist, non-fatty foodstuff.

LINER:
A white, supercalendered glassine paper. Specially designed for high speed conversion, punching and perforation. Good calliper consistency allows accurate kiss-diecutting. The papers translucent qualities are perfectly suited to automatic label applicators.

Thickness	63 micron ±5%
Basic Weight	70 gsm ±5%

SHELF LIFE:
2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.

Unit A2 Hubert Road, Brentwood, Essex CM14 4JE
Tel: 01277 281 910 Fax:0800 085 6992
sales@bakermaterials.co.uk www.bakermaterials.co.uk

REGISTRATION NO. 1116854 IN ENGLAND
REGISTERED OFFICE:UNIT A2 HUBERT ROAD BRENTWOOD ESSEX CM14 4JE
VAT Registration No. GB 230 7578 65