

Specification Sheet

BF154

ZIG ZAG WHITE PEEL FSC

R100



FACE:

A matt, white, surface sized supercalendered printing paper based on low-chlorine bleached pulp (ECF pulp). Designed for the manufacture of continuous label forms for use in dot matrix printers and laser printers. Good print quality by all the conventional printing technologies, excellent multicolour printing results. . FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, LicenceCode:C004451).

Thickness 79 micron $\pm 5\%$

Basic weight 75 gsm $\pm 5\%$

ADHESIVE:

R100 A rubber based removable adhesive. For general purpose applications on a wide variety of substrates. Features good initial tack and superior removeability. Excellent low temperature performance. Application to porous substrates or prolonged exposure to UV light may adversely affect clean removeability.

Initial Tack Low

Final Adhesion Low

Min. App.Temp -20°C

Temp Range -40°C to $+80^{\circ}\text{C}$

UV Resistance Poor

Complies with FDA 175.105 recommendations for contact with dry and wet, non-fatty foodstuffs.

LINER:

A one side coated bleached kraft paper.

Suitable for fanfold and roll to sheet conversion and all products requiring good body and lay flatness.

Thickness 76 micron $\pm 5\%$

Basic Weight 75 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.