

# Specification Sheet

BF902

NATURAL BOIS - BIODEGRADABLE

S9500



## FACE:

A natural uncoated brown laid kraft, printing paper composed of PEFC pulp. Suitable for sustainable labelling of premium goods due to its natural image. Printable by most conventional printing methods.

Thickness 88 micron  $\pm 5\%$

Basic weight 90 gsm  $\pm 5\%$

## ADHESIVE:

S9500 is an acrylic based biodegradable adhesive with good initial tack and adhesion on a wide variety of substrates.

Initial Tack Good

Final Adhesion Good

Min. App.Temp  $+5^{\circ}\text{C}$

Temp Range  $-20^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$

UV Resistance Moderate

The film complies with European food regulation: 1935/2004/EC for direct contact with dry- non fatty foodstuff.

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 63 micron  $\pm 5\%$

Basic Weight 70 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.