

Specification Sheet

BF905

GLOSS CLEAR FILM BIODEGRADABLE

S692N



FACE:

A gloss clear film specifically constructed to be biodegradable/compostable. With a print receptive top coating this material is printable by flexo and rotogravure printing.

Thickness 45 micron $\pm 5\%$

Basic weight 64 gsm $\pm 5\%$

ADHESIVE:

S692N A clear permanent acrylic adhesive, featuring excellent UV resistance and weatherability, together with good adhesion performance, even on apolar substrates.

Initial Tack Medium

Final Adhesion High

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -20°C to $+80^{\circ}\text{C}$

UV Resistance Moderate

Complies with the European food regulation 1935/2004/EC for direct food contact with dry, non-fatty foodstuff.

Complies with DIN EN 13432 biodegradability and compostability regulation and is OK Compost certified under the tracking number S259.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 53 micron $\pm 5\%$

Basic Weight 60 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.