

Specification Sheet

BM050

SATIN ACETATE WHITE (TTP)

PERMANENT



FACE:

A white, fine quality acetate cloth with a satin finish. Suitable for printing using flexo, letterpress and offset lithography. Because of its highly absorbant nature it may require an adjustment in ink quality. Thermal Transfer printable with selected ribbons. Suggested uses include labels for shoes and clothing.

Thickness 160 micron $\pm 5\%$

Basic weight 125 gsm $\pm 5\%$

ADHESIVE:

A permanent modified acrylic aqueous dispersion adhesive, specifically designed for textile labelling.

Initial Tack Medium

Final Adhesion High

Min. App.Temp $+10^{\circ}\text{C}$

Temp Range -20°C to $+60^{\circ}\text{C}$

UV Resistance N/A

Not suitable for labelling silk, leather, suede and PVC fabrics

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 56 micron $\pm 5\%$

Basic Weight 64 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.