Specification Sheet

BM082
SEMI-GLOSS BLOCKOUT - BLACK PERMANENT

FACE:
A white woodfree machine finished printing paper, backprinted with opaque dense black prior to adhesive coating.This is a high opacity product designed to obliterate and possibly correct unwanted or redundant text.

Thickness	85 micron ±5%
Basic weight	100 gsm ±5%

ADHESIVE:
An acrylic based permanent adhesive suitable for application on most substrates. Also recommended for curved substrates, eg small diameter glass ampoules. Ideal for high speed conversion and production of complex shaped labels.

Initial Tack	High
Final Adhesion	Very high
Min. App.Temp	+10°C
Temp Range	-20°C to +80°C
UV Resistance	Excellent

Complies with FDA 175.105 and with BgVV XIV recommendations for indirect contact with foodstuff.

LINER:
A supercalendered siliconised glassine paper, with high mechanical resistance to tearing.

Thickness	57 micron ±5%
Basic Weight	51 gsm ±5%

SHELF LIFE:
2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.

Unit A2 Hubert Road, Brentwood, Essex CM14 4JE
Tel: 01277 281 910 Fax:0800 085 6992
sales@bakermaterials.co.uk www.bakermaterials.co.uk

REGISTRATION NO. 1116854 IN ENGLAND
REGISTERED OFFICE:UNIT A2 HUBERT ROAD BRENTWOOD ESSEX CM14 4JE
VAT Registration No. GB 230 7578 65