

Specification Sheet

BM1010

MATT SILVER VOID PET HIGH PERF (02-266)

P60



FACE:

A matt silver void polyester is designed as a security label that offers an instant VOID message upon removal of the label. This material offers improved adhesion to low surface energy substrates and requires less application time prior to removal and evidence of tampering. Designed to accept conventional ink and thermal transfer printing.

Thickness 50 micron $\pm 10\%$

Basic weight

ADHESIVE:

High performance permanent acrylic adhesive with very good chemical, humidity and UV resistance. High initial tack and excellent adhesion to most substrates combined with good low temperature adhesion.

Initial Tack High

Final Adhesion Very high

Min. App.Temp $+4^{\circ}\text{C}$

Temp Range -60°C to $+125^{\circ}\text{C}$

UV Resistance Very good

Automotive Approved.

LINER:

A polycoated glassine liner

Thickness 74 micron $\pm 10\%$

Basic Weight 82 gsm $\pm 10\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.