

Specification Sheet

BM1056

WHITE GLOSS PET (01-725)

PAT 1



FACE:

A gloss white print receptive polyester offering excellent dimensional stability combined with good solvent, humidity, elevated temperature and UV resistance. Designed to accept conventional ink and provides superior thermal transfer print quality with crisp definition at low burn temperatures with resin and wax/resin ribbons.

Thickness 50 micron $\pm 10\%$

Basic weight

ADHESIVE:

A strong, permanent acrylic adhesive with proven performance for standard labels, nameplates and other similar uses. It has high cohesion and good resistance to heat, cold water and UV. It also has good quick-stick, peel and shear strength with excellent adhesion to low surface energy surfaces. It is designed for high speed automatic label application.

Initial Tack Medium

Final Adhesion High

Min. App.Temp $+4^{\circ}\text{C}$

Temp Range -40°C to $+149^{\circ}\text{C}$

UV Resistance Good

Automotive Approved.

UNDERWRITERS LABORATORY RECOGNITION

LINER:

A supercalendered siliconised blue glassine paper, with high mechanical resistance to tearing.

Thickness 66 micron $\pm 10\%$

Basic Weight 71 gsm $\pm 10\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.