

Specification Sheet

BM1084

VELVET LEXAN POLYCARBONATE 75MM (09
NPL



FACE:

A matt clear velvet lexan overlaminating film offers excellent anti-glare, impact and scuff resistance. Ideal for automotive and electronic labelling.

Not recommended for outdoor use.

Thickness 75 micron $\pm 5\%$

Basic weight

ADHESIVE:

A strong, permanent ultra clear solvent acrylic adhesive exhibiting excellent optical clarity and UV stability. Offers excellent chemical, humidity and temperature resistance.

Initial Tack Medium

Final Adhesion High

Min. App.Temp $+4^{\circ}\text{C}$

Temp Range -46°C to $+135^{\circ}\text{C}$

UV Resistance Very good

Automotive Approved

LINER:

A clear silicone coated polyester liner designed to ensure adhesive smoothness when used with ultra-clear overlaminating films.

Thickness 25 micron $\pm 5\%$

Basic Weight

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.