

Specification Sheet

BM1116

GLOSS WHITE 5YR DESTRUCT ACRYLIC (08
P99



FACE:

A gloss white cast acrylic which has excellent destructibility and tamper evidence. The face film has excellent UV, humidity and elevated temperature resistance. Can be thermal transfer printed but for conventional inks, corona treatment may be required.

Thickness 50 micron $\pm 10\%$

Basic weight

ADHESIVE:

P99 is a high performance acrylic based adhesive with a low initial tack and high final adhesion to high surface energy substrates. The low initial tack enables repositionability on initial application.

Initial Tack Low

Final Adhesion High

Min. App.Temp $+4^{\circ}\text{C}$

Temp Range -25°C to $+150^{\circ}\text{C}$ (12 hours) $+250^{\circ}$ (5 Minutes)

UV Resistance Excellent

LINER:

A blue polycoated glassine liner. The one side PE coated liner ensures adhesive smoothness and ease of release. Suitable for high speed dispensing.

Thickness 80 micron $\pm 10\%$

Basic Weight 96 gsm $\pm 10\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.