

# Specification Sheet

BM1122

MATT CLEAR PET (01-702)

NPL



## FACE:

A matt clear print receptive polyester with excellent dimensional stability combined with good solvent, humidity, elevated temperature and UV resistance. This overlaminating film is designed to accept conventional inks and thermal transfer printing with resin and wax / resin ribbons.

Thickness 25 micron  $\pm 10\%$

Basic weight

## ADHESIVE:

An ultra clear UV stable permanent acrylic adhesive with excellent chemical, humidity and temperature resistance. Specially developed for clear film applications requiring excellent optical clarity, flow out properties and resistance to ooze.

Initial Tack Medium

Final Adhesion High

Min. App.Temp  $+4^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+135^{\circ}\text{C}$

UV Resistance Good

UL Approved & Automotive approved.

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 69 micron  $\pm 10\%$

Basic Weight 82 gsm  $\pm 10\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.