

Specification Sheet

BM1157

3M MATT WHITE PET 50MM (G61SB)

250E



FACE:

A matt white polyester, topcoated for improved ink receptivity and designed for thermal transfer printing. It is printable by all standard methods including flexography, hot foil, letterpress and screen process. Typical applications include electrical appliances, electronics and automotive parts

Thickness 50 micron $\pm 5\%$

Basic weight

ADHESIVE:

A UV stable, permanent, solvent acrylic all-purpose adhesive. Formulated with high tack and high ultimate adhesion it is particularly suitable for non polar substrates.

Initial Tack High

Final Adhesion Very high

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -40°C to $+150^{\circ}\text{C}$

UV Resistance Good

UL and cUL approved (File Number MH18072)

LINER:

A double sided white glassine liner.

Thickness 56 micron $\pm 7.5\%$

Basic Weight 62 gsm $\pm 6.5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.