

# Specification Sheet

BM1165

3M CI MATT WHITE PET 50MM (H01CH)

HP100



## FACE:

A matt white polyester with a print receptive durable topcoat designed for thermal transfer printing. The matt coating gives excellent resistance to solvents, heat, moisture, and ageing.

Thickness 50 micron  $\pm 5\%$   
Basic weight

## ADHESIVE:

An all purpose permanent solvent based acrylic adhesive.

Initial Tack High  
Final Adhesion High  
Min. App.Temp  $+5^{\circ}\text{C}$   
Temp Range  $-40^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$   
UV Resistance Good

This product has UL approval.

BS5609 Approved

## LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 75 micron  $\pm 10\%$   
Basic Weight 90 gsm  $\pm 4\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.