

Specification Sheet

BM1215

INKJET PREMIUM GLOSS PAPER
PERMANENT



FACE:

A white, high gloss, coated paper with a micro porous and highly absorbent surface structure specifically designed for "photo quality" ink jet printing. Designed specifically for VP ink jet digital printer from VIP Color Tech.

This product is suitable for a wide range of industrial applications, where on demand colour coding, or picture coding is required.

Thickness 110 micron $\pm 5\%$

Basic weight 95 gsm $\pm 5\%$

ADHESIVE:

A general purpose acrylic based permanent adhesive with excellent performance on a wide variety of substrates including packaging materials, plastic films, PE and PP containers.

Labels can also be used on chilled products/dry substrates.

Initial Tack High

Final Adhesion Very high

Min. App.Temp 0°C

Temp Range -20°C to +80°C

UV Resistance Good

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

LINER:

A white, supercalendered glassine paper. Specially designed for high speed conversion, punching and perforation. Good calliper consistency allows accurate kiss-diecutting.

The papers translucent qualities are perfectly suited to automatic label applicators.

Thickness 55 micron $\pm 5\%$

Basic Weight 60 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.