

Specification Sheet

BM1216

INKJET PREMIUM MATT WHITE PP
HIGH TACK



FACE:

A matt white cavitated top coated polypropylene specifically designed for high quality ink jet printing. Also printable by UV letter press, UV screen, gravure, hot stamping and thermal transfer printing. Suitable for labelling plastic containers.

Thickness 60 micron \pm 5%

Basic weight 45 gsm \pm 5%

ADHESIVE:

A rubber based permanent adhesive with high tack adhesion on apolar surfaces.

Initial Tack High

Final Adhesion Very high

Min. App.Temp 0°C

Temp Range -10°C to +70°C

UV Resistance

BS5609 approved for chemical drum labelling.

ISEGA approved for direct contact with dry or moist, non-fatty foodstuffs.

LINER:

A one side siliconised white glassine paper.

Thickness 55 micron \pm 5%

Basic Weight 62 gsm \pm 5%

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.