Specification Sheet

BM1219 INKJET GLOSS WHITE PP PERMANENT



FACE:

A gloss white top coated polypropylene film specifically designed for water-based Inkjet printing. Quick drying with good smudge and moisture resistance.

Thickness 89 micron \pm 5% Basic weight 73 gsm \pm 5%

ADHESIVE:

A clear permanent acrylic adhesive, featuring excellent UV resistance and weatherability, together with good adhesion performance, even on apolar substrates.

Initial Tack High

Final Adhesion Very high

Min. App.Temp +5°C

Temp Range -20°C to +80°C

UV Resistance Good

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 54 micron \pm 5% Basic Weight 61 gsm \pm 5%

SHELF LIFE:

1 year when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.