

# Specification Sheet

BM262  
GLOSS CLEAR PET 50MM  
PERMANENT



## FACE:

A transparent polyester film with a print receptive top coated surface. Designed for sheet fed and continuous laser printing, dot matrix and thermal transfer.

Thickness 52 micron  $\pm 5\%$   
Basic weight 70 gsm  $\pm 5\%$

## ADHESIVE:

An acrylic based, clear, permanent adhesive. Good temperature, water, solvent and chemical resistance.

Initial Tack Very High  
Final Adhesion High  
Min. App.Temp 0°C  
Temp Range -20°C to +80°C  
UV Resistance Good

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

## LINER:

A one side coated bleached kraft paper.

Thickness 110 micron  $\pm 5\%$   
Basic Weight 98 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.