

Specification Sheet

BM302

MATT BLACK VINYL

PERMANENT



FACE:

A monomeric matt finished calendered polyvinyl chloride (PVC) soft handle plasticised film, exhibiting excellent mechanical resistance and flexibility. Cadmium free.

Thickness 80 micron $\pm 5\%$

Basic weight

ADHESIVE:

A permanent modified acrylic aqueous dispersion with excellent resistance to UV-light and ageing.

Initial Tack High

Final Adhesion Very high

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -30°C to $+90^{\circ}\text{C}$

UV Resistance Excellent

Compliance with EN 71/3 (application on toys) and European packaging directive 94/62/EC (heavy metals).

ISEGA approved for direct contact with dry or moist, non-fatty foodstuffs.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 63 micron

Basic Weight 72 gsm

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.