

Specification Sheet

BM304
GLOSS CLEAR VINYL
PERMANENT



FACE:

A clear gloss plasticized calendered polyvinyl chloride (PVC) soft handle film, exhibiting excellent mechanical resistance and flexibility.

Thickness 80 micron $\pm 5\%$
Basic weight 108 gsm $\pm 5\%$

ADHESIVE:

A permanent modified acrylic aqueous dispersion with excellent resistance to UV-light and ageing.

Initial Tack High
Final Adhesion Very high
Min. App.Temp $+5^{\circ}\text{C}$
Temp Range -30°C to $+90^{\circ}\text{C}$
UV Resistance Excellent

Compliance with EN 71/3 (application on toys) and European packaging directive 94/62/EC (heavy metals).

ISEGA approved for direct contact with dry or moist, non-fatty foodstuffs.

LINER:

A calendered, siliconised white kraft paper.

Thickness 136 micron $\pm 5\%$
Basic Weight 135 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 20°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.