

# Specification Sheet

BM406

MATT WHITE LASER PET

PERMANENT



## FACE:

A matt white polyester, top coated to be computer imprintable and thermal transfer print-receptive. Specifically designed for hot fuse sheet fed laser printing where there is a requirement for variable information on a durable label for manufactured part labelling, tracking, stock control, racked storage identification etc.

Thickness 58 micron  $\pm 5\%$

Basic weight 75 gsm  $\pm 5\%$

## ADHESIVE:

A permanent, acrylic aqueous, dispersion. Specially designed for labelling of HDPE drums and other rough substrates.

Initial Tack High

Final Adhesion Very high

Min. App.Temp 0°C

Temp Range -20°C to +70°C

UV Resistance Poor

UV resistance of this adhesive is limited.

BS5609 Approved

## LINER:

A white one sided siliconised kraft paper, that has good layflat qualities and can be back-printed.

Thickness 112 micron  $\pm 5\%$

Basic Weight 120 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at 20° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.