

Specification Sheet

BM510
PREMIUM CAST COAT 80
PERMANENT



FACE:

A cast, supergloss coated, woodfree paper. Used for premium quality labels such as cosmetics, toiletries, etc, where a top quality appearance is called for.

Thickness 88 micron $\pm 5\%$
Basic weight 80 gsm $\pm 5\%$

ADHESIVE:

A permanent modified water based acrylic adhesive. Improved performance on a wide range of substrates including apolar surfaces and at low temperature.

Initial Tack High
Final Adhesion Very high
Min. App.Temp 0°C
Temp Range -10°C to +65°C
UV Resistance Good

ISEGA approved for direct contact with dry or moist, non-fatty foodstuffs.
Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

LINER:

A supercalendered siliconised glassine paper, with high mechanical resistance to tearing.

Thickness 51 micron $\pm 5\%$
Basic Weight 58 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.