

Specification Sheet

BM516
GLOSS BLACK LITHO
PERMANENT



FACE:

A coated paper with a gloss black finish on one side. Mainly used for promotional work, product identification, and price marking plus a wide range of miscellaneous uses where a background colour is demanded for a long or short run without the need to colour wash on press.

Thickness 90 micron $\pm 5\%$
Basic weight 80 gsm $\pm 5\%$

ADHESIVE:

A permanent, acrylic adhesive with strong initial adhesion, high tack and good cohesion. Designed for all purpose applications on moist, low temperature surfaces. Excellent resistance to icewater.

Initial Tack High
Final Adhesion Very high
Min. App.Temp $+5^{\circ}\text{C}$
Temp Range -10°C to $+75^{\circ}\text{C}$
UV Resistance Good

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 68 micron $\pm 5\%$
Basic Weight 80 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.