

Specification Sheet

BM731

MATT WHITE TC PP 120MM

HIGH TACK



FACE:

A matt white bia-axially orientated, top-coated, polypropylene film.

Thickness 120 micron $\pm 5\%$

Basic weight 93 gsm $\pm 5\%$

ADHESIVE:

A permanent acrylic water based adhesive. Good adhesion to wet surfaces at low temperatures. Especially designed for glass containers with excellent resistance to immersion in water/ice.

Initial Tack Very High

Final Adhesion High

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -10°C to $+75^{\circ}\text{C}$

UV Resistance Moderate

ISEGA approved for direct contact with dry or moist, non-fatty foodstuffs.

Complies with FDA 175.105 recommendations for direct contact with dry non-fatty foodstuff.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 67 micron $\pm 5\%$

Basic Weight 78 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.