

Specification Sheet

BM794A

HIGH GLOSS LAYFLAT

PERMANENT



FACE:

A cast coated woodfree paper with a high gloss finish. Suitable for high-quality multicolour copy and laser printing. This product is designed for variable information printing where there is a requirement to project a quality image. It may also be used on occasions for high quality reel to sheet applications.

Thickness 85 micron $\pm 5\%$

Basic weight 80 gsm $\pm 5\%$

ADHESIVE:

A permanent modified acrylic aqueous dispersion.

Initial Tack High

Final Adhesion Very high

Min. App.Temp $+5^{\circ}\text{C}$

Temp Range -10°C to $+100^{\circ}\text{C}$

UV Resistance Good

LINER:

A one side coated bleached kraft paper.

Thickness 69 micron $\pm 5\%$

Basic Weight 66 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.