

Specification Sheet

BM806RE
GLOSS RED VINYL
PERMANENT



FACE:

A monomeric gloss finished calendered polyvinyl chloride (PVC) soft handle plasticised film, exhibiting excellent mechanical resistance and flexibility. Cadmium free.

Thickness 70 micron $\pm 10\%$
Basic weight 97 gsm $\pm 10\%$

ADHESIVE:

A permanent modified acrylic aqueous dispersion.

Initial Tack Medium
Final Adhesion High
Min. App.Temp $+10^{\circ}\text{C}$
Temp Range -30°C to $+120^{\circ}\text{C}$
UV Resistance Excellent

Complies with FDA 175.105 recommendations for indirect contact with dry and non-fatty foodstuff.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 55 micron $\pm 10\%$
Basic Weight 65 gsm $\pm 10\%$

SHELF LIFE:

3 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.