

Specification Sheet

BT315
GLOSS WHITE DIGI PP
HIGH TACK



FACE:

A gloss white top coated polypropylene surface treated for Indigo printing process.

Thickness 59 micron \pm 5%

Basic weight 57 gsm \pm 5%

ADHESIVE:

A rubber based, permanent adhesive. Excellent adhesive performance on a wide variety of substrates including apolar, slightly rough and curved substrates. Particularly good performance at lower temperatures, eg labelling of chilled products.

Initial Tack High

Final Adhesion Very high

Min. App.Temp 0°C

Temp Range -40°C to +70°C

UV Resistance N/A

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry and moist non-fatty foodstuff.

BS5609 part II Marine use approval.

LINER:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness 63 micron \pm 5%

Basic Weight 70 gsm \pm 5%

SHELF LIFE:

1 year when stored at 22° C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.