

# Specification Sheet

BF265

WBIJ BRIGHT SILVER TC PET

S692N



## FACE:

BF265 - A Metalized PET film high absorbent surface structure specifically designed for Water based inkjet printing.

Thickness 98 micron  $\pm 5\%$

Basic weight 77 gsm  $\pm 5\%$

## ADHESIVE:

S692N A clear permanent acrylic adhesive, featuring excellent UV resistance and weatherability, together with good adhesion performance, even on apolar substrates.

Initial Tack High

Final Adhesion High

Min. App.Temp  $+5^{\circ}\text{C}$

Temp Range  $-20^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$

UV Resistance Excellent

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry and moist non-fatty foodstuff.

## LINER:

A white, supercalendered glassine paper. Specially designed for high speed conversion, punching and perforation. Good calliper consistency allows accurate kiss-diecutting. The papers translucent qualities are perfectly suited to automatic label applicators.

Thickness 54 micron  $\pm 5\%$

Basic Weight 61 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.