

Specification Sheet

BM681

MATT WHITE DESTRUCTIBLE FILM
HIGH TACK



FACE:

A matt white topcoated ultra destructible film which has a higher tensile strength compared to conventional Ultra destructs. It has a fast conversion speed and reliable waste removal on press. This is suitable for conventional and thermal transfer printing. Typical applications include asset labelling, security seals and pharmaceutical box seal labels

Thickness 50 micron $\pm 5\%$

Basic weight 33 gsm $\pm 5\%$

ADHESIVE:

A high performance adhesive offering a very good adhesion to high and low surface energy surfaces.

Initial Tack High

Final Adhesion Very high

Min. App.Temp $+4^{\circ}\text{C}$

Temp Range -40°C to $+80^{\circ}\text{C}$

UV Resistance Moderate

This product has been designed for the medicinal product packaging labels to assist pharmaceutical manufacturers meet the European requirements of the Falsified Medicines Directives 2011/62/EU

LINER:

A blue super calendared glassine release liner. This offers great die cutting performance

Thickness 68 micron $\pm 5\%$

Basic Weight 71 gsm $\pm 5\%$

SHELF LIFE:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.

Unit A2 Hubert Road, Brentwood, Essex CM14 4JE
Tel: 01277 281 910 Fax:0800 085 6992
sales@bakermaterials.co.uk www.bakermaterials.co.uk

REGISTRATION NO. 1116854 IN ENGLA
REGISTERED OFFICE:UNIT A2 HUBERT ROAD BRENTWOOD ESSEX CM14 4
VAT Registration No. GB 230 7578

Rev date