

# Specification Sheet

BM1147

GLOSS WHITE POLYESTER

PERMANENT



## FACE:

Bright white gloss finish polyester. Fully waterproof, tear, scuff and solvent resistant. Ideal for water resistance applications such as chemical drum and container labelling, outdoor signage and labels. Suitable for toner/laser, thermal transfer, litho, flexo etc.

Thickness 53 micron  $\pm 5\%$

Basic weight 75 gsm  $\pm 5\%$

## ADHESIVE:

Initial Tack High

Final Adhesion High

Min. App.Temp  $+5^{\circ}\text{C}$

Temp Range  $-40^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$

UV Resistance Good

BS5609 Part I & II Approved.

## LINER:

Kraft paper liner ideal for sheeting.

Thickness 60 micron  $\pm 5\%$

Basic Weight 90 gsm  $\pm 5\%$

## SHELF LIFE:

2 years when stored at  $22^{\circ}\text{C}$  / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the companies conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate users responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.